


Lastest valid version 2023

NATURBAG

Product code: JL/JV/UL/UV

Paper designed for producing small bags

This paper provides high tensile strength and tear resistance. It offers characteristic gloss for the design of **small bags** and printing. It is available in both plain and ribbed finish, made of 100% virgin long fibre. Quality: JL/JV standard UL/UV for printing.



Main Advantages

FOOD CONTACT

Our whole range of papers is **certified for food contact**. Bfr and FDA certifications according to the corresponding standard.

FORMATION

This paper offers a **closed sheet** which reduces the need to use large quantities of inks, glues etc. Guaranteeing the best printing quality.

RUNNABILITY

This paper range stands out for its ability to withstand **high mechanical strength** and high-speed handling processes.

Technical specifications

SUBSTANCE			ISO-536	g/m ²	32	35	40	45	50
MOISTURE			ISO-287	%	5,5	5,5	5,5	5,5	6,0
TENSILE INDEX	MD	ISO-1924		N.m/g	85	85	90	95	95
	CD	ISO-1924		N.m/g	40	45	45	45	50
BURST			ISO-2758	kPa	115	125	160	190	210
BURST INDEX			ISO-2758	kPa.m ² /g	3,6	3,6	4,0	4,2	4,2
COBB-60			ISO-535	g/m ²	25	26	26	26	27
STRETCH AT BREAK	MD	ISO-1924		%	1,5	1,6	1,8	1,9	2,1
	CD	ISO-1924		%	3,2	3,5	3,8	4,1	4,5
TEAR INDEX (SM+ST)/2			ISO-1974	(mN.m ² /g)	6,9	7,1	7,3	7,7	8,3

Tariff code:4804.31.58

Controlled atmosphere according ISO 554-1976 (50% h.r., 23°C)
Nominal weight + -4%
Humidity + -2
Typical values -It is not a contractual document

Finishing Options



Smurfit Kappa Sangüesa paper fulfills framework Regulation 1935/2004/EC, Commision Regulation (EC) Nº 2023/2006 Council of Europe Resolution AP (2002)1, and German Recommendation BfR XXXVI, for materials and papers in contact with foodstuffs

