

## GlobalTAC Technical Information

23-06-2025 EN SI

<b>Product</b>	<b>GT PE LASER MATT / PERMANENT D / KRAFT SPECIAL 120 / SOLID UNPRINTED</b>
Sales Code	HZI/GDP4/HZQ/W0
Product use	Designed for information labeling, especially used on drums logistic labeling. Due to the exceptional thickness and stability, large label sizes can be used. Certified by HP Indigo Industrial media for Indigo digital offset printing.

### Typical technical values

<b>Face</b>		<b>GT PE LASER MATT</b>	
Product	White matt high pigmented computer imprintable polyethylene film.		
Substance	115	g/m²	DIN 53352
Caliper	178	µm	DIN 53370
Elongation MD	430	%	DIN 53455
Elongation CD	470	%	DIN 53455
Opacity	92	%	DIN 53146/1
Printability	Due to the surface properties, the film is pre-printable by screen, offset, flexography, letterpress, electrophotography, electrography, digital offset and dotmatrix. Thermal transfer with selected ribbons. Inks for filmic substrates are recommended. Laser and copier printable: specially developed for medium and high volumes.		
<b>Adhesive</b>		<b>PERMANENT D</b>	
Type	Permanent		
Composition	Waterborne acrylic		
Tack min	9	N	FTM 9
Shear min	10	h	FTM 8
<b>Backing</b>		<b>KRAFT SPECIAL 120</b>	
Product	White woodfree kraft backing paper.		
Substance	120	g/m²	ISO 536
Caliper	112	µm	ISO 534
Tensile strength MD	8	kN/m	ISO 1924
Tensile strength CD	4	kN/m	ISO 1924
<b>Performance</b>			
Total caliper	307 µm		

Minimum labelling temperature	5 °C
Service temperature	-20 to 100 °C
Shelf life	From date of manufacture: 12 months, under FINAT defined storage conditions (+20-25°C and 40-50% RH). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.
Disclaimer	<p>The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.</p> <p>This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.</p> <p>All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.</p> <p>This publication replaces all previous versions. All information is subject to change without notice.</p>